



## **SPEEDFACE - 5 PRO**







Touch Screen



RFID



WiF



LAN



LISE



Access Control

# Facial Attendance and Access Control

# Storage Capacity

Face ID Capacity	50,000
Card Capacity	50,000
Log Capacity	2,00,000



### **Features**

DualCoreARM Cortex Processor

Remotely Firmware Upgradation.

5-inch IPS display all-sight LCD touch screen with 480\*854 resolution.

IP54 Grade Highly finished slim device.

Highly reliable and durable

Recognition speed 0.5 seconds

# **SPEEDFACE - 5 PRO**

#### Communication Interface

Communication	WIFI, TCP/IP, USB
---------------	-------------------

#### **Biometric**

Push Data	YES
Remote firmware update	YES
FAR	0.01%
FAR	0.01%
Accuracy ratio	99.99%
Processor	Dual Core ARM Cortex
OS	Linux
Verification time	<=1 second
RF card options	Wiegand 26/34



Auto Focus



low light Verification



Long Distance Verification

# Audio/Visual

LCD	5.0" IPS touch screen display
Shutter type	Electronic Rolling Shutter
Language	English

Software Web & Cloud

## Access control

Relay	YES
Wiegand output	YES



Time Attendance



Access Control



Employee Self Service



Mobile App

### Power & Environment

Operating Temperature	-10°c ~ 50°c
Power	12V DC / 2A
Dimension	190.00 x 87.53 x 17.00 mm

**Disclaimer**: Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

BiomaxOfficial



Connect with us on

BioMax Security





